## Digital Display Solutions / PWD Series



Designed with LED touch screen technology, the Purplewave Interactive Flat Panel Display is a dynamic and engaging solution for both education and business environments. Encouraging interactive communication, its technology facilitates learning as well as information sharing.

- · Perfect 4K resolution
- · Front audio stereophonic speaker
- · Industrial grade aluminium frame
- Multiple signal input HDMI, VGA, Video, YPbPr, TV etc.
- · Infrared touch technology for rich writing experience
- · Password / Pattern Lock protected
- · 4mm protect glass and anti-scratch
- · 20 points touch, <5~8ms response
- Support APK install & authorize management, permit or forbidden application





## **OPS Support**

All our products in this series have compliance with OPS (Open Pluggable Standard). OPS will empower your screens with enhanced processing power and ability to choose Windows or Android as your operating system to fit your specific application.



## **Touch Support**

Our touch screens are compatible with this series. Infrared (IR) Touch Screens is designed to equip your current product with user-interactivity allowing the display to be smart display and many interactive applications to be enjoyed by the end users. The design also permits any person to overlay the touch screen on the display easily.



## Suitable Design For Class Rooms, Board Room, Meeting Rooms

Use Purplewave's interactive flat panel displays to bring your workforce together. Our Ultra HD products can be used for interactive presentations, brainstorming and training.

	Technic	cal Speciation		
Parameters	PWD55TRX	PWD65TRX	PWD75TRX	
Diagonal Size	55"	65"	75"	
Backlight Type	D LED			
Aspect Ratio	16:09			
Pixel Pitch	0.28(H) x 0.28(W)	0.372 (H) X 0.372 (W)	0.4296(H) x 0.4296(L)	
Response	5ms to 8ms			
Resolution	3840 x 2160			
Contrast Ratio	5000:1 (Static) / 100k:1 (Dynamic)	4000:1 (Static) / 100k:1 (Dynamic)	6000:1 (Static) / 100k:1 (Dynamic)	
Brightness (cd/m2	400cd/m2			
Display area	1209mm(H) x 680mm(V)	1428.48mm(H) x 803.52mm(V)	1650.24mm(H) X 928.26mm(V)	
Color	16.7 Million color	1.07 Bill	ion color	
View Angle	H/V: 178o/178o			
		System		
os	Android 9.0			
СРИ	Cortex A53*4, 1.5GHz	Quad core A55, 1.5GHz	Quad-core A55, 1.5GHz	
RAM		3GB		
FLASH (Memory)	32GB			
	-, I,	/O Port		
Rear Input	LAN IN*1, COAX*1, RS-232*1, PC-AUDIO*1, VGA IN*1			
	HDMI IN*2, TOUCH USB*2, USB2.0*2, MIC*1			
Front Input	USB2.0*2, TOUCH USB*1, HDMI IN*1			
Output	Earphone OUT*1			
	Med	lia Format		
Audio	Mp3, WMA, WAV, APE, FLAC, AAC, OGG, M4A, 3GPP			
Video	H.264, VP 8, RV, WMV, AVS, H.263, MPEG4			
Picture	JPG, BMP, PNG			
	Touc	h Features		
Touch Type		Infrared Touch		
Glass	4mm, Physical 7 grade tempered glass, Explosion proof,anti glare			
Transmittance	>92%			
Response Time	≤5 ~ 8ms			
Touch Precision	≤1mm			
Touch Object	All Opaque object, such as finger, pen etc			
MTF	60 million touch by each points			
Minimum Touch Object	≥ 1mm			
Anti-light	Incandescent lamp (220V,100W) Distance > 350mm,Sunlight illumination<90000Lux			
Interface		USB		
		Audio		
Speaker		2 x 15W(max) Stereo		

	OPS PC (optional)		
CPU	Core i5		
Memory	4GB / 8GB		
Hard disk	SSD: 240GB		
I/O port	USB2.0*2, USB3.0*2, MIC*1, LINE OUT*1, RJ45*1, VGA*1,HDMI*1		
	Tech Features		
Language	English		
Video Format	PAL, NTSC		
Working Mode	24×7 hrs		
Display Light	60,000* hrs		
Frequency	Horizontal Frequency : 20 ~ 82KHz (Anolog & Digital)Vertical Frequency: 55 ~ 75Hz		
Optimum Resolution	3840 x 2160 @ 30HZ		
Support Resolution	3840 x 2160, 1920 x 1080, 1680 x 1050, 1600 x 1200, 1440x 1050, 1360 x 768, 1280 x 1024		
	1280 x 768, 1024 x 768, 832 x 624, 800 x 600, 720 x 400,600 x 480		
Video Format	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 4K		
	Function Features		
Amazing OSD	Humanity beautiful OSD, Touch control		
Multiple Control	Support remote control, keyboard, RS232, Touch control		
Touch OSD	Touch slide from bottom to start the hidden OSD menu		
Sunlight Readable	Suit for lots of places, it can readable at sunlight		
Touch	20 points touch		
Multiple I/O	Support HDMI / VGA / CVBS / YPbPr / Display Port / TV		
Input Auto Scan	Auto-scan the input signal, and countdown tips		
Customize Mode	Preset Standard, Warm, Cinema, Meeting work mode and support customize		
Airplay	iPhone, iPad wireless display on TAIO monitor by airplay		
Software	Whiteboard, Mirror display, Comment etc		
	Physical Features		
Power Supply	AC 100 ~ 240V, 50-60Hz, 1.1A		
Consumption	Max ≤ 300W, Normal ≤ 220W, Standby ≤ 0.5W		
Body material	Gray frame, Black metal cover		
Color	Black		
Temperature	Work: 0°C ~50°C, Storage : -20° ~ 60°C		
Humidity	Work: 10% to 90%, Storage: 0 to 95% (Non Condensing)		
Noise	Working Noise<50dBA		
Product Dimension	1479.9*923.6*106.1mm	1699.2*1038.1*90.2mm	
VESA hole	400 x 200 mm(4*M8 screw)	600 x 200 mm(4*M8 screw)	
Weight	NW: 38Kg±1.5Kg, GW: 47Kg±1.5Kg		
Package Dimension	1600 x 1025 x 215mm	1870*1150*220MM	
	Other		
Accessories	Remote control*1, Power Cord*1, Wi-Fi antenna *1		
Option	HDMI, DVI, VGA, BNC, Floor stand set		
Certification	BIS, CE, ISO9001, UL		